

# **TC-508**

## Professional Two-way Radio Affordable & Reliable









- Tough & Light-weight
- Robust & Reliable
- Longer Battery Life
- **■** Enhanced Voice Quality



## TC-508

## **Professional Two-way Radio**

## **Leading Features**

#### ■ Tough & Light-weight

TC-508 has a light-weight but exceptionally strong body, allowing it to be carried about easily and to survive harsh conditions.

#### Robust & Reliable

TC-508 is built to survive the hard knocks, drops and some lough environments of its users. It meets or exceeds the HYT 5-year ALT test.

#### ■ Longer Battery Life

TC-508 is equipped with a 1650mAh battery that enables you to transmit and receive, on a 5-5-90 basis, for up to 14 hours.

#### **■** Enhanced Voice Quality

TC-508 employs advanced voice technologies to better the sound quality during your communication.

#### **Main Functions**

High/Low Power Switch

Wide/Narrow Band Switch

Monitor

CTCSS/CDCSS and Squelch Tall Elimination

Channel Scan

**Battery Save** 

**Low Battery Alert** 

**Busy Channel Lockout** 

Time-out Timer (TOT)

PC Programmable

Wired Clone

Squelch Levels Selectable







### **Recommended Applications**

- Hospitality
- Manufacturing
- Retail

- Education
- Construction
- Security

#### Accessories

Standard Accessories LI-lon Battery Belt Clip Repid-Rate Charger (for Li-Ion Battery)

Power Adapter Antenna

#### Optional Accessories



LHon Battlery (1300mAh RJ 1301



Vehicle Power Adapte CHV09



Remote Speaker Microphone SM08M3



Earbud with on-MIC PTT & VOX ESM12



D-earset with in-Line
MIC & VOY EHM15



D-sarset with Boom MIC & VOX EHM16



Earplece with on-MIC PTT & Transparent Acoustic Tube EAN12



Receive-Only Estplece with Transperent Acquestic Tube (for use with remote speaker microphysical PSSOR



Nylon Carrying Cas (not swivel)(black) NCN001



Racelve-Only Earplece (for use with remote speaks microphone) ESS07

Note: Pictures above are for reference only and may vary from actual product.

#### General

Frequency Range(MHz)	VHF: 146-174 UHF: 400-470/450-470/350-400
Channel Capacity	16
Channel Spacing(KHz)	25 /12.5
Operating Voltage(V)	7.4
Battery	1650mAh (Li-Ion Battery)
Battery Life (5-5-90 Duty Cycle)	14 hours
Frequency Stability(ppm)	±25
Operating Temperature(°C)	-20+65
Antenna Impedance(Ω)	50 :
Dimensions (H×W×D)(with battery, without antenna)(mm)	113×54×35
Weight (with antenna & battery)(g)	280

Sensitivity	≤0.251uV/0.282uV
Adjacent Channel Selectivity	70dB/60dB
Intermodulation	65dB
Spurious Response Rejection	70dB
5/N	45dB/40dB
Rated Audio Power Output	0.5W (Speaker Impedance: 16 Ohm)
Rated Audio Distortion	≤5% (0.5W)
Conducted Spurious Emission	-57dBm < 1GHz -47dBm > 1GHz

Power Output	5W/2W(VHF) 4W/2W(UHF)
Modulation	16K0F3E/11K0F3E
Spurious and Harmonics	≤-26dBm (<1G)
FM Noise	40/35dB
Audio Distortion	≤5 %
Modulation Limiting	≤5KHz (25KHz) ≤2.5KHz (12.5KHz)

All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.



#### **Hytera Communications Corporation Limited**

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057 Http://www.hytera.com

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Your Local Dealer