

PD665

DMR handheld radio



With six programmable keys

With its lightweight metal housing and support of digital and analog mobile radio, the handheld radio PD665 series is the ideal companion for migrating to digital mobile radio. Compared to the PD605, the PD665 has a bright LCD display and six programmable keys.

Small, lightweight and narrow

The radios of the PD6 series are only 27 mm deep, making them particularly compact. The housings are trimmed in a high-quality aluminum frame and are comfortable to carry for long periods with a weight of only 310 g.

Versatile

The PD665 has both an analog mode and a digital mode and is compatible with analog radio systems, as a consequence it is very easy for you to change to the digital age.

Technical Data PD665

General data	
Frequency range	VHF: 136 – 174 MHz UHF: 400 – 527 MHz
Supported operating modes	<ul style="list-style-type: none"> ▪ DMR Tier II (ETSI TS 102 361-1/2/3 ▪ Simulcast ▪ XPT Digital Trunking ▪ DMR Tier III (ETSI TS 102 361-1/2/3/4) ▪ Analog
Number of channels	1024
Number of zones	64
Channel spacing	12.5 / 20 / 25 kHz (analog) 12.5 kHz (digital)
Operating voltage	7.4 V (nominal)
Batteries available	1500 mAh (lithium-ion battery) 2000 mAh (lithium-ion battery)
Battery service life (5-5-90 duty cycle, high transmitting power, standard battery)	approx. 11 hours (analog) approx. 16 hours (analog) (with 1500 mAh) approx. 22 hours (digital) (with 2000 mAh)
Frequency stability	± 0.5 ppm
Antenna impedance	50 Ω
Dimensions (H x W x D, without antenna)	119 x 54 x 27 mm
Weight (with antenna and standard battery)	approx. 310 g
Programmable keys	6
LCD display	160 x 128 pixels, 65,536 colors, 1,8 inches, 4 rows

Environmental conditions	
Operating temperature range	- 30 °C to + 60 °C
Storage temperature range	- 40 °C to + 85 °C
ESD	IEC 61000-4-2 (Level 4), ± 8 kV (contact), ± 15 kV (air)
Protection against dust and moisture	IP67
Shock and vibration resistance	MIL-STD-810 C / D / E / F / G
Relative humidity	MIL-STD-810 C / D / E / F / G

GPS (optional)	
Time to first fix (TTFF)	< 1 Minute (cold start) < 10 seconds (warm start)
Horizontal accuracy	< 10 meter

Transmitter	
Transmitting power	VHF: 1 / 5 W UHF: 1 / 4 W
Modulation	11 K0F3E to 12.5 kHz 14 K0F3E to 20 kHz 16 K0F3E to 25 kHz
4FSK digital modulation	12.5 kHz (data only): 7K60FXD 12.5 kHz (data and voice): 7K60FXW
Interfering signals and harmonics	- 36 dBm (< 1 GHz) - 30 dBm (> 1 GHz)
Modulation limiting	±2.5 kHz at 12.5 kHz ±4.0 kHz at 20 kHz ±5.0 kHz at 25 kHz
Noise cancellation	40 dB to 12.5 kHz 43 dB to 20 kHz 45 dB to 25 kHz
Adjacent channel selectivity	60 dB to 12.5 kHz 70 dB to 20 / 25 kHz
Audio sensitivity	+ 1 dB to - 3 dB
Nominal audio distortion	≤ 3 %
Digital vocoder type	AMBE +2™

Receiver	
Sensitivity (analog)	0.22 µV (12 dB SINAD) 0.22 µV (typical) (12 dB SINAD) 0.4 µV (20 dB SINAD)
Sensitivity (digital)	0.22 µV / BER 5 %
Adjacent channel selectivity TIA-603	60 dB at 12.5 kHz / 70 dB at 20 and 25 kHz
ETSI	60 dB at 12.5 kHz / 70 dB at 20 and 25 kHz
Intermodulation TIA-603	70 dB at 12.5 / 20 / 25 kHz
ETSI	70 dB at 12.5 / 20 / 25 kHz
Spurious response rejection TIA-603	70 dB at 12.5 / 20 / 25 kHz
ETSI	70 dB at 12.5 / 20 / 25 kHz
Signal-noise ratio (S/N)	40 dB at 12.5 kHz 43 dB at 20 kHz 45 dB at 25 kHz
Nominal audio power output	0.5 W
Nominal audio distortion	≤ 3 %
Audio sensitivity	+ 1 dB to - 3 dB
Conducted spurious emission	< - 57 dBm

All technical information was determined at the factory and in accordance with the corresponding standards. Subject to change on the basis of continuous development.



Hytera Mobilfunk GmbH

Address: Fritz-Hahne-Straße 7, 31848 Bad Münder, Germany
Tel.: + 49 (0)5042 / 998-0 Fax: + 49 (0)5042 / 998-105
E-mail: info@hytera.de | www.hytera-mobilfunk.com



SGS Certificate DE11/81829313

Hytera Mobilfunk GmbH reserves the right to modify the product design and the specifications. In case of a printing error, Hytera Mobilfunk GmbH does not accept any liability. All specifications are subject to change without notice.

Encryption features are optional and have to be configured separately; they are also subject to German and European export regulations.

HYT Hytera are registered trademarks of Hytera Co. Ltd. ACCESSNET® and all derivatives are protected trademarks of Hytera Mobilfunk GmbH. © 2017 Hytera Mobilfunk GmbH. All rights reserved.