

## PD565

DMR handheld radio



### Compact and reliable

The PD565 from Hytera impresses with its compact design, its range of functions and its excellent value for the money. With the support of digital and analog mobile radio, the PD565 is your perfect companion for entering the world of professional digital mobile radio.

### Light and easy to operate

The radios of the PD5 series are particularly ergonomic and easy to operate. With a weight of only 280 g, the PD565 offers you a high level of mobility comfort.

### Long battery service life

The PD565 was developed in compliance with the ETSI Digital Mobile Radio (DMR) standard. With the optionally available 2000-mAh battery, it will even be 20 hours.

# Technical Data PD565

General data	
Frequency range	VHF: 136 – 174 MHz UHF: 400 – 470 MHz
Supported operating modes	<ul style="list-style-type: none"> <li>▪ DMR Tier II (conventional DMR)</li> <li>▪ Simulcast</li> <li>▪ XPT Digital Trunking</li> <li>▪ Analog</li> </ul> DMR Tier II according to ETSI TS 102 361-1/2/3
Number of channels	512
Number of zones	32
Channel spacing	12.5 / 20 / 25 kHz (analog) 12.5 kHz (digital)
Operating voltage	7.4 V (nominal)
Standard battery	1500 mAh (lithium-ion battery)
Battery service life (5-5-90 duty cycle, high transmitting power, standard battery)	approx. 11 hours (analog) approx. 16 hours (analog) (with 1500 mAh) approx. 22 hours (digital) (with 2000 mAh)
Frequency stability	± 0.5 ppm
Antenna impedance	50 Ω
Dimensions (H x W x D, without antenna)	115 x 54 x 27 mm
Weight (with antenna and standard battery)	approx. 280 g
Programmable keys	6
LCD display	monochrome LCD display, 3 lines

Environmental conditions	
Operating temperature range	-30 °C to +60 °C
Storage temperature range	-40 °C to +85 °C
ESD	IEC 61000-4-2 (Level 4), ± 8 kV (contact), ± 15 kV (air)
Protection against dust and moisture	IP54
Shock and vibration resistance	MIL-STD-810 C / D / E / F / G
Relative humidity	MIL-STD-810 C / D / E / F / G

Transmitter	
Transmitting power	VHF: 1 / 5 W UHF: 1 / 4 W
Modulation	11 K0F3E at 12.5 kHz 14 K0F3E at 20 kHz 16 K0F3E at 25 kHz
4FSK digital modulation	12.5 kHz (data only): 7K60FXD 12.5 kHz (data and voice): 7K60FXW
Interfering signals and harmonics	- 36 dBm (< 1 GHz) - 30 dBm (> 1 GHz)
Modulation limiting	±2.5 kHz at 12.5 kHz ±4.0 kHz at 20 kHz ±5.0 kHz at 25 kHz
Noise cancellation	40 dB at 12.5 kHz 43 dB at 20 kHz 45 dB at 25 kHz
Adjacent channel selectivity	60 dB at 12.5 kHz 70 dB at 20 / 25 kHz
Audio sensitivity	+ 1 dB to - 3 dB
Nominal audio distortion	≤ 3 %
Digital vocoder type	AMBE +2™

Receiver	
Sensitivity (analog)	0.22 µV (12 dB SINAD) 0.22 µV (typical) (12 dB SINAD) 0.4 µV (20 dB SINAD)
Sensitivity (digital)	0.22 µV / BER 5 %
Adjacent channel selectivity TIA-603	60 dB at 12.5 kHz / 70 dB at 20 and 25 kHz
ETSI	60 dB at 12.5 kHz / 70 dB at 20 and 25 kHz
Intermodulation TIA-603	70 dB at 12.5 / 20 / 25 kHz
ETSI	70 dB at 12.5 / 20 / 25 kHz
Spurious response rejection TIA-603	70 dB at 12.5 / 20 / 25 kHz
ETSI	70 dB at 12.5 / 20 / 25 kHz
Signal-noise ratio (S/N)	40 dB at 12.5 kHz 43 dB at 20 kHz 45 dB at 25 kHz
Nominal audio power output	0,5 W
Nominal audio distortion	≤ 3 %
Audio sensitivity	+ 1 dB to - 3 dB
Conducted spurious emission	< - 57 dBm

All technical information was determined at the factory and in accordance with the corresponding standards. Subject to change on the basis of continuous development.



Hytera Mobilfunk GmbH

Address: Fritz-Hahne-Straße 7, 31848 Bad Münder, Germany  
Tel.: + 49 (0)5042 / 998-0 Fax: + 49 (0)5042 / 998-105  
E-mail: info@hytera.de | www.hytera-mobilfunk.com



SGS Certificate DE11/81829313

Hytera Mobilfunk GmbH reserves the right to modify the product design and the specifications. In case of a printing error, Hytera Mobilfunk GmbH does not accept any liability. All specifications are subject to change without notice.

Encryption features are optional and have to be configured separately; they are also subject to German and European export regulations.

HYT Hytera are registered trademarks of Hytera Co. Ltd. ACCESSNET® and all derivatives are protected trademarks of Hytera Mobilfunk GmbH. © 2017 Hytera Mobilfunk GmbH. All rights reserved.